

PO

| | | | |
|--|---|--------------------------------------|--------------------------|
| | | | |
| | 26000 | | |
| | <p>PO</p> <p>PO</p> | <p>C N</p> <p>PO</p> <p>mi Gclim</p> | - |
| | | | |
| | | | |
| | <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| | | | |
| | | | |

| | | | | | |
|---|---|--|---------|-----|-------|
| | | | | / | |
| 1 | 1 | 1.2 *1.5 | | 18 | 320 / |
| 2 | 2 | 0.9 *1.5 | | 5.4 | 320 / |
| 3 | | 1 | | 1 | |
| 4 | 5 | 5 23AWG 250MHz 305 / | 0.005mm | 1 | 380 / |
| 5 | | RVV 2*1 | | 200 | 2.4 / |
| 6 | | IP 8 2 320M 160M SMART 2.0 2 | | 1 | 456 / |
| 7 | | 200 1/2.7 CMOS 1920 1080@30FPS; 0.005lux@(F1.6,AGC ON) 0.001Lux @(F1.6,AGC ON);0 Lux with IR;150 4.8-115mm,23 AC24V,IP66 | | 4 | 480 / |

| | | | | |
|----|--|--------|---|-------|
| 8 | | 6TB | 2 | 380 / |
| 9 | | 8 | 1 | 110 / |
| 10 | | 12V 2A | 4 | 15 / |
| 11 | | | 1 | |

